




제품구분	P3624FG	P3608FG	P3516FGD
형상			
Hardware			
Switching Fabric	8.8 Gpps	12.8 Gbps	12.8 Gbps
Throughput	6.5 Mpps	4.1 Mbps	6.5 Mpps
Flash memory	16MB	16MB	16MB
DRAM	64MB	64MB	64MB
Uplink(125G/10G)	2	2	2
10/100/1000 Mpps			
10/100 Mpps	24	8	16
PoE			
GBIC(SFP) Slot or Giga TX			
Dimension (mm)	437 X 260 X 44	437 X 260 X 44	250 X 180 X 39
Power Consumption	17W	11.42W	30W
IPv6	O	O	O
Software			
VLAN			
Max VLAN	4K	4K	4K
LACP	O	O	O
Filtering, Security			
Mac address	16K	16K	16K
Mac limitation	O	O	O
STP	O	O	O
RSTP	O	O	O
MSTP	O	O	O
ACL(Access Control List)	O	O	O
802.1x support	O	O	O
Radius Accounting	O	O	O
TACACS+	O	O	O
SSH (Secure SHell)	O	O	O
Bandwidth Management & QoS			
802.1p QoS	O	O	O
Packet Classification & Marking	O	O	O
# of Queue	O	O	O
strict queue	O	O	O
Management			
SNMPV1, V2	O	O	O
RMON	O	O	O
Telnet, TFTP, FTP	O	O	O
Port mirroring	O	O	O
CLI (command line interface)	O	O	O
Multicasting			
IGMP	O	O	O
IGMP v2	O	O	O
IGMP snooping	O	O	O