






제품구분	E3208E	E3002F-24P	E3002F-8P	E3224C	E3224D
형상					
Hardware					
Switching Fabric	12.8Gbps	12.8Gbps	5.6Gbps	12.8Gbps	12.8Gbps
Throughput	1.19Mpps	6.5Mpps	3.2Mpps	9.5Mpps	6.5Mpps
Flash memory		32MB	32MB	32MB	32MB
DRAM		128MB	128MB	256MB	256MB
10/100 Mbps		24(UTP)	8(UTP)	24	24
10/100/1000 Mbps					
GBIC(SFP) Slot or Giga TX		2	2	4(Fixed Combo Ports)	2(Fixed Combo Ports)
POE		15.4(258.7W)/PoE+(30W)	15.4(258.7W)/PoE+(30W)		
Dimension (mm)	268 X 128 X 44	437 X 360 X 44	437 X 360 X 44	437 X 261 X44	437 X 261 X44
Power Redundancy		X	X	X	X
Power Consumption	16.9W	318W	128.4W	16W	12W
IPv6		O	O	O	O
Software					
VLAN					
Max VLAN	4K	4K	4K	4K(256)	4K(256)
Link Aggregation(802.3ad)	O			O	O
LACP		O	O		
Filtering, Security					
Mac address	16K	16K	16K	16K	16K
Mac limitation	O	O	O	O	O
STP	O	O	O	O	O
RSTP	O	O	O	O	O
MSTP		O	O	O	O
ACL(Access Control List)		O	O	O	O
802.1x support		O	O	O	O
Radius Accounting		O	O	O	O
TACACS+		O	O	O	O
SSH (Secure SHell)		O	O	O	O
Bandwidth Management & QoS					
802.1p QoS		O	O	O	O
Packet Classification & Marking		O	O	O	O
strict queue		O	O	O	O
Management					
SNMPV1, V2		O	O	O	O
RMON		O	O	O	O
Telnet, TFTP, FTP		O	O	O	O
Port mirroring		O	O	O	O
CLI (command line interface)		O	O	O	O
Multicasting					
IGMP	O	O	O	O	O
IGMP v2	O	O	O	O	O
IGMP Snooping	O	O	O	O	O