

제품구분	E3024L	U3108L
형상		
Hardware		
Switching Fabric	12.8Gbps	3.2Gbps
Throughput	9.5Mpps	2.5Mpps
Flash memory	32MB	16MB
DRAM	128MB	64MB
10/100 Mbps		8
10/100 Mbps(VDSL Port)	24	8
GBIC(SFP) Slot or Giga TX	2	
POE		
Dimension (mm)	438 X 320 X 66	435 X 300 X 22
Power Redundancy	○	○
Power Consumption	80W	25.7W
IPv6		
Software		
VLAN		
Max VLAN	4K	4K
Link Agregation(802.3ad)	○	○
Filtering, Security		
Mac address	16K	8K
Mac limitation	○	○
STP	○	○
RSTP	○	○
MSTP	○	○
ACL(Access Control List)	○	○
802.1x support	○	○
Radius Accounting	○	○
TACACS+	○	○
SSH (Secure SHell)	○	○
Bandwidth Management & QoS		
802.1p QoS	○	○
Packet Classification & Marking	○	○
strict queue	○	○
Management		
SNMPV1, V2	○	○
RMON	○	○
Telnet, TFTP, FTP	○	○
Port mirroring	○	○
CLI (command line interface)	○	○
Multicasting		
IGMP	○	○
IGMP v2	○	○
IGMP snooping	○	○