

제품구분	CS3400	CE7010
형상		
Hardware		
Switching Fabric	128Gbps Switch Fabric, 80Gbps (full-duplex) Non-Blocking Switch Fabric	128Gbps Switch Fabric, 80Gbps (full-duplex) Non-Blocking Switch Fabric
Throughput	59Mpps	95Mpps
Flash memory	256MB Flash Memory	256MB Flash Memory
DRAM	512MB Main Memory	512MB Main Memory
Interface	1000Base-X(SFP) 16port or 10/100/1000Base-T 16port or 10GBase-R(XFP) 4port or E1 12port . CS3400-4F: 1GE 4port SFP module (1000Base-X) . CS3400-4T: 1GE 4port Tx module (1000Base-T)	1000Base-X(SFP) 24port or 10/100/1000Base-T 24port 10GBase-R(SFP+) 4port . LIU1G-6F: 1GE 6port SFP module (1000Base-X)
Dimension (mm)	437 x 330 x44	437mm(W) x 320mm(D) x 110 mm(H)
Power Redundancy	○	○
Power Consumption	Max. 54W	
IPv6	○	○
Software		
VLAN		
Max VLAN	4k	4K
LACP	○	○
Filtering, Security		
Mac address	16K	16K
Mac limitation	○	○
STP	○	○
RSTP	○	○
MSTP	○	○
ACL(Access Control List)	○	○
802.1x support	○	○
Radius Accounting	○	○
TACACS+	○	○
SSH (Secure SHell)	○	○
Bandwidth Management & QoS		
802.1p QoS	○	○
Packet Classification & Marking	○	○
strict queue	○	○
Management		
SNMPV1, V2	○	○
RMON	○	○
Telnet, TFTP, FTP	○	○
Port mirroring	○	○
CLI (command line interface)	○	○